

# Dial Reading Viscometer

The original viscometer that set the world standard

- Easy-to-select speeds
- Electronic drive means quiet, reliable operation
- Analog display
  - Shows % torque
  - Use Factor Finder to convert reading to centipoise
- Simple to use, easy setup
- 2-Year limited warranty
- Accuracy:  $\pm 1.0\%$  of range
- Repeatability:  $\pm 0.2\%$

## What's Included

- Instrument
- 6 spindles (RV/HA/HB) or 4 spindles (LV)
- Spindle guard leg\*
- Lab stand (Model G)
- Carrying case

\*Not applicable to HA or HB torque models

## Optional Accessories

- Viscosity standards
- RV/HA/HB-1 spindle
- Quick Action lab stand
- Temperature Bath
- Small Sample Adapter
- UL Adapter
- Thermosel
- Spiral Adapter
- DIN Adapter
- Quick Connect/Extension Links
- Vane Spindles



Easy Speed Adjustment and On/Off Control



VISCOSITY RANGE cP(mPa•s)			SPEEDS	
MODEL	Min.	Max.	RPM	Number of Increments
LVT	1†	2M	.3-60	8
RVT	100††	8M	.5-100	10
HAT	200†	16M	.5-100	10
HBT	†	64M	.5-100	10

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles. †† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.  
 M = 1 million cP = Centipoise mPa•s = Millipascal•seconds